



## **GATEWAY SYSTEM FOR VOICE COMMUNICATION AND CONTROLLING METHOD THEREOF**

### **BACKGROUND OF THE INVENTION**

#### **1. Field of the Invention**

**[001]** The present invention relates to a gateway system for a voice communication between terminals connected with the Internet, and more particularly, to a gateway system for voice communication in which a voice signal transmitted from terminals are compressed to be transmitted to the Internet and the compressed voice signal transmitted from the Internet is uncompressed to be transmitted to the terminals, thereby enabling voice communication between terminals, ~~and its~~. The invention also relates to a controlling method of the gateway system.

#### **2. Description of the Background Art**

**[002]** Generally, there are two communication methods: a voice communication method applied between terminals (i.e., telephone or facsimile, etc.) connected with a public switch telephone network (PSTN) and a data communication method applied between terminals (i.e., Internet phone, personal computer, etc.) connected with a local area network (LAN) that is connected with the PSTN or with a dedicated network.

**[003]** Recently, as communication equipment and techniques are being progressed, the voice communication and the data communication are made through a single communication network. That is, an Internet phone and a PC are respectively connected with the LAN connected with Internet protocol-based Internet, so that voice communication is made through the internet phone while data communication is made through the PC.

**[004]** Generally, communication protocols such as a ring signal period and a

communication system between exchanges are differently set according to regions or nations. But, in case of the Internet phone connected with the Internet on the basis of the Internet protocol (TCP/IP), since voice communication is performed through the Internet, without requiring the PSTN for use only for voice communication, regardless of a private branch exchange (PBX) pursuant to the communication protocols, no expense incurs with respect to maintaining and managing the PSTN.

**[005]** In a situation with the network formed as described above, in order to perform voice communication through the Internet on a real time basis, the voice signal is to be compressed and packetized to a small size and then transmitted to the Internet, and the compressed voice signal as received from the Internet is to be restored to its original voice signal. In this respect, a CODEC for performing a function to compress the voice signal and restore the compressed voice signal to its original signal must be installed at the Internet phone.

**[006]** The communication protocols for the voice communication through the Internet includes recommendation H.323 incorporated by ITU-T (International Telecommunication Union-Telecommunication Standardization Sector), and the recommendation H.323 uses recommendation Q.931 for connection establishment. Developed for ISDN (Integrated Services Digital Network), the recommendation Q.931 processes the voice signal as well as a call in the Internet phone itself.

**[007]** A recently developed multimedia Internet protocol system (MIPS) to support the recommendations H.323 and Q.931 of the protocols and enable communications through the Internet includes a gateway system enabling communication between Internet phones by transmitting a voice signal packet through the Internet.

**[008]** However, when the Internet phone connected with the gateway system

of the conventional art constructed as described above is desired to communicate with other Internet phone, a voice signal should be compressed and packetized by a CODEC installed in the Internet phone itself to be transmitted, and the compressed voice signal should be received and restored to its original voice signal.

**[009]** Therefore, the gateway system in accordance with the conventional art is disadvantageous in that since the voice signal is processed by the CODEC installed in the Internet phone no matter that the Internet phone communicates with an Internet phone or a telephone set located in a remote place through the Internet or that the Internet phone communicates with other Internet phone commonly connected with a single LAN, the voice communication between the Internet phones ~~are~~ is not performed on a real time basis. Moreover, only the Internet phone including the CODEC can perform voice communication.

### **SUMMARY OF THE INVENTION**

**[010]** Therefore, an object of the present invention is to provide a gateway system for voice communication for rendering IP terminals connected to a local area network (LAN) to communicate with each other, rendering PSTN terminals connected to a PSTN to communicate with each other, rendering the IP terminals and the PSTN terminals to communicate with each other, rendering the IP terminals and the PSTN terminals to voice-communicate with PSTN terminals and IP terminals of a different area with each other through the Internet, and its controlling method.

**[011]** Another object of the present invention is to provide a gateway system for voice communication for rendering IP terminals that ~~supports~~ support the Internet protocols and ~~does~~ do not have require a CODEC to voice-communicate with different IP terminals or with PSTN terminals, and ~~its~~ to provide a controlling method for the gateway system.

**[012]-**

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, there is provided a gateway system for voice communication of a communication system for performing communication among PSTN terminals connected to a PSTN, IP terminals connected to an Internet protocol-based local area network (LAN) and remote terminals of a different area connected to the Internet; the gateway system including: a PSTN gateway for rendering the PSTN terminals and the IP terminals to communicate with each other; and an inter-gateway for rendering the IP terminals and the PSTN terminals through the PSTN gateway to communicate with the remote terminals through the Internet.

**[013]** In order to achieve the above and other objects, there is also provided a gateway system for voice communication including: a PSTN terminal connected to a PSTN for communication; an IP terminal connected to a local area network (LAN) for communication; a PSTN gateway for rendering the PSTN terminal and the IP terminal to communicate with each other; and an inter-gateway for rendering the IP terminal and the PSTN gateway to which the PSTN terminal is connected, to communicate with an IP terminal and a PSTN terminal of a different area through the Internet.

**[014]** In order to achieve the above and other objects, there is also provided a method for controlling a gateway system for voice communication including the steps of: connecting a first terminal connected with an Internet protocol-based LAN with a first inter-gateway that converts a protocol of the first terminal and connects it with the Internet; connecting the first inter-gateway and a second inter-gateway as the first terminal is connected with the first inter-gateway and transmits an ID of the second gateway connected with the Internet; transmitting an Internet phone number

of a second terminal connected with the second inter-gateway by the first terminal as the first terminal and the first and the second inter-gateways are connected with each other, and receiving a call signal from the second terminal; and performing voice communication between the first and the second terminals.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

**[015]** The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

**[016]** In the drawings:

**[017]** Figure 1 is a schematic view showing a construction of a gateway system for voice communication in accordance with the present invention;

**[018]** Figure 2 is a view showing a ~~state-of~~ process of transmitting and receiving of signals between Internet phones connected with the Internet for voice communication in accordance with the present invention; and

**[019]** Figure 3 is a detailed view showing the ~~state-of~~ process of transmitting and receiving of signals between Internet phones connected with the Internet for voice communication in accordance with the present invention of Figure 2 in accordance with the present invention.

### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

**[020]** Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

**[021]** Figure 1 is a view showing a construction of a communication system

adopting a gateway system for voice communication in accordance with the present invention.

**[0221]** As shown in the drawing, a communication system of an area 'A' includes a gateway system '100A' for connecting the PSTN and a local area network (LAN) with the Internet, a telephone set ~~'10A'~~ '10A' connected with the PSTN and Internet phones '20A-1, 20A-2,...,20A-N', and, likewise, a communication system of an area 'B' includes a gateway system '100B' for connecting the PSTN and the LAN with the Internet, a telephone set '10B' connected with the PSTN, and Internet phones '20B-1, 20B-2,..., 20B-N'.

**[0231]** The gateway system 100A of the area 'A' includes a PSTN gateway 30A for converting a protocol of a signal transmitted to or received from a telephone set 10A connected with the PSTN to render the Internet phones 20A-1, 20A-2,..., 20A-N connected with the telephone 10A and the LAN to communicate with each other; and an inter-gateway 40A for compressing a signal processed by the PSTN gateway 30A and signals received from the Internet phones 20A-1, 20A-2,..., 20A-N to transmit them to terminals (i.e., 10B, 20B-1, 20B-2,..., 20B-N) connected with the Internet, uncompressing a signal transmitted from the Internet to transmit it to the terminals 20A, 20A-1, 20A-2,...20A-N, to thereby perform communication between the terminals 10A, 20A-1, 20A-2,..., 20A-N, 10B, 20B-1, 20B-2,..., 20B-N.

**[0241]** The gateway system ~~400b~~ 100B of the area 'B' is symmetrically constructed with the gateway system 100A of the area 'A'.

**[0251]** In the communication system adopting the gateway system constructed as described above in accordance with an embodiment of the present invention, a voice signal packet is transmitted and received between the Internet phones 20A-1, 20A-2,..., 20A-N and the Inter-gateway 40A, while a compressed voice signal packet is transmitted and received between the inter-gateway 40A and

the inter-gateway 40B of the other area through the Internet.

**[026]** That is, according to the gateway system of the present invention, voice communication between the Internet phones connected with the LAN is performed by a voice signal that is not compressed, and only when the voice communication is made through the Internet, the voice signal transmitted from the Internet phone is compressed and transmitted to the Internet and the compressed voice signal is received from the Internet and uncompressed to be transmitted to the Internet phone by using the Inter-gateway, so that the voice communication between the Internet phones can be effectively performed.

**[027]** Figure 2 is a view showing a ~~state of~~ process of transmitting and receiving ~~of~~ signals between Internet phones connected with the Internet for voice communication in accordance with the present invention.

**[028]** With reference to Figure 3 ~~2~~, first, when the Internet phone 20A-1 transmits a connection request message (SETUP) to the inter-gateway 40A-1 through the LAN (1), the inter-gateway 40A allocates one of a standby (idle) channels among a plurality of CODEC channels thereof and transmits a connection request response message (SETUP\_ACK) to the Internet phone 20A-1 (2).

**[029]** At this time, in case that the CODEC channels are all in an active state, the inter-gateway 40A transmits a connection request rejection message (SETUP\_REJ) to the Internet phone 20A-1.

**[030]** Upon receipt of the connection request response message (SETUP\_ACK), the Internet phone 20A-1 transmits an ID of the inter-gateway 40B and the number of the Internet phone 20B-1 with which the Internet phone 20A-1 is intended to be connected to the inter-gateway 40A (3)(4).

**[031]** After receiving the ID of the inter-gateway 40B, when the inter-gateway 40A converts the ID of the inter-gateway 40B to an Internet protocol address (IP

address) by using a pre-set mapping table and transmits a connection request message (SETUP) to the inter-gateway 40B corresponding to the IP address (a), the inter-gate way 40B allocates an idle one of a plurality of CODEC channels thereof and transmits a connection request response message (SETUP\_ACK) to the inter-gateway 40A (b).

**[032]** Upon receipt of the connection request response message (SETUP\_ACK), the inter-gateway 40A transmits the number of the ~~internet~~ Internet phone 20B-1 with which the ~~internet~~ Internet phone 20A-1 is intended to be connected ~~with~~ to the inter-gateway 40B (c). Then, the inter-gateway 40B transmits a connection request message (SETUP) to the ~~internet~~ Internet phone 20B-1 corresponding to ~~the~~ that number (i).

**[033]** Upon receipt of the connection request message from the inter-gateway 40B, when the ~~internet~~ Internet phone 20B-1 rings and a user picks up the receiver thereof, a connection proceeding message (CALL\_PROCEEDING) is outputted to the inter-gateway 40B (ii). The inter-gateways 40B and 40A that are sequentially receiving the connection proceeding message transmit the connection proceeding message to the Internet phone 20A-1 (d)(5).

**[034]** And then, after a predetermined time elapses, when the Internet phone 20B-1 transmits a connection completion message (CONNECT) to the inter-gateway 40B (iii), the inter-gateway 40B transmits a connection completion response message (CONNECT\_ACK) to the Internet phone 20B-1 (iv) and transmits a connection completion message (CONNECT) to the inter-gateway 40A (e).

**[035]** When the inter-gateway 40A transmits a connection completion message (CONNECT) to the Internet phone 20A-1 (6), the Internet phone 20A-1 transmits a connection completion response message (CONNECT\_ACK) to the inter-gateway 40A (7).



**[036]** Accordingly, the voice channels of the Internet phones 20A-1 and 20B-1 and the inter-gateways 40A and 40B become active, by which the voice communication is made between the Internet phones.

**[037]** In this respect, since the Internet phones 20A-1 and 20B-1 do not include a CODEC, the voice is simply packetized and then transmitted to the inter-gateways 40A and 40B. Then, the inter-gateways compress the voice signal and transmit and receive the voice signal each other through an allocated CODEC channel, and then uncompress the compressed voice signal as received and transmit it to the Internet phones, thereby making voice communication between the Internet phones.

**[038]** Figure 3 is a detailed view showing the ~~state-of~~ process shown in Figure 2 of transmitting and receiving of signals between Internet phones connected with the Internet for voice communication ~~in accordance with the present invention of Figure 2~~ in accordance with the present invention

**[039]** First, in order to connect the Internet phone 20A-1 with the intended Internet phone 20B-1, when the Internet phone is off the hook, a connection request message (SETUP) is transmitted to the inter-gateway 40A and a call signal is initiated (1).

**[040]** Upon receipt of the connection request message (SETUP), the inter-gateway 40A transmits a connection request response message (SETUP\_ACK) to the Internet phone 20A-1 and then is changed to an overlap received state. The Internet phone 20A-1 receiving the connection request response message (SETUP\_ACK) is changed to an overlap sending state (2).

**[041]** While the Internet phone 20A-1 and the inter-gateway 40A are in the overlap sensing state and in the overlap received state, when the Internet phone 20A-1 transmits an ID of the inter-gateway 40B to the inter-gateway 40A, the inter-

gateway 40A receives the ID of the inter-gateway 40B (3) and then transmits a connection request message (SETUP) to the inter-gateway 40B (a).

**[042]** After receiving the connection request message from the inter-gateway 40A (a), the inter-gateway 40B transmits the connection request response message to the inter-gateway 40A and is changed to a call present state.

**[043]** After a predetermined time elapses, when the Internet phone 20A-1 transmits the number of the Internet phone 20B-1 with which itself intends to be connected with the inter-gateway 40A, the inter-gateway 40A transmits the number of the Internet phone 20B-1 with which the Internet phone 20A-1 intends to be connected with, to the inter-gateway 40B (c).

**[044]** Then, the inter-gateway 40B transmits a connection request message (SETUP) to the Internet phone 20B-1 corresponding to ~~the~~ that number (i). When the Internet phone 20B-1 receives the connection request message from the inter-gateway 40B, it is changed to the call present state (i), transmits the connection proceeding message to the inter-gateway 40B and then is changed to the call signal received state (ii). At the same time, the Internet phone 20B-1 rings (ii-1).

**[045]** Upon receipt of the connection proceeding message (ii), the inter-gateway 40B transmits the connection proceeding message to the inter-gateway 40A and is changed to a call signal received state (d).

**[046]** Upon receipt of the connection proceeding message, the inter-gateway 40A transmits the connection proceeding message to the Internet phone 20A-1 and is changed to a call signal transmitting state (5).

**[047]** Upon receipt of the connection proceeding message, the Internet phone 20A-1 is changed to a call signal received state (5).

**[048]** Meanwhile, when the Internet phone 20B-1 is off the hook, the connection completion response message is transmitted to the inter-gateway 40B

and is changed to the connection request state (iii).

**[049]** After receiving the connection completion message, the inter-gateway 40B-1 transmits the connection completion response message to the Internet phone 20B-1, so that the Internet phone 20B-1 activates the voice channel, and transmits the connection completion message to the inter-gateway 40A so that the Inter-gateway 40A becomes active (e).

**[050]** Upon receipt of the connection completion message, the inter-gateway 40A transmits the connection completion message to the Internet phone 20A-1 and is changed to an active state (6). Upon receipt of the connection completion message, the Internet phone 20A-1 transmits the connection completion response message to the inter-gateway 40A, so that the voice channel becomes active (7).

**[051]** Accordingly, the voice channel of the Internet phones 20A-1 and 20B-1 and the inter-gateways 40A and 40B becomes active, and voice communication is made between the Internet phones.

**[052]** In this respect, in case that the Internet phones 20A-1 and 20B-1 and the gateways 40A and 40B receive a different message other than the corresponding message (1-1, 2-1, 4-1, a-1, b-1, c-1 and d-1), they are changed to a standby state.

**[053]** In the above described embodiment of the gateway system of the present invention, voice communication between the Internet phones are taken as example, but proceedings that a telephone set connected with the PSTN communicates with a different terminal are performed in the same manner.

**[054]** As so far described, according to the gateway system for voice communication and its controlling method of the present invention, the voice signal transmitted from the terminals ~~are~~ is compressed and transmitted to the Internet and the compressed voice signal as transmitted from the Internet is uncompressed and transmitted to the terminals, by which the terminals connected with the Internet

simply perform voice communication without a CODEC in the terminals.

**[055]** As the present invention may be embodied in several forms without departing from the spirit or essential characteristics thereof, it should also be understood that the above-described embodiments are not limited by any of the details of the foregoing description, unless otherwise specified, but rather should be construed broadly within its spirit and scope as defined in the appended claims, and therefore all changes and modifications that fall within the meets and bounds of the claims, or equivalence of such meets and bounds are therefore intended to be embraced by the appended claims.